Sectra Table

Technical specifications

Quality and clinical relevance through interaction and visualization

Interaction with virtual representations of real-life bodies based on clinical imaging provides a deeper understanding and insight into anatomy as well as the functions and processes inside the body.

A combination of the highly relevant medical education cases in Sectra Education Portal and the possibility of intuitive interaction with the images maximizes learning and the potential for group engagement and interaction.

First-class touch interaction and visualization

The Sectra Table is a large 65" monitor with an electrical tilt function, and a 4K capacitive touchscreen, that vastly improves the interaction with the visualized data.

SECTRA

Width: 1430 mm Height: min. 795 mm

Height: max. 1185 mm (in table mode)

Depth: 900 mm (in table mode)

QLed technology turns light into breathtaking color with extreme depth and bold contrast. It's an ideal complement to Sectra Education Portal. It facilitates collaborative learning, and helps students critical thinking and analytical skills.

Key features & benefits

- Large 65" monitor
- 4K resolution
- Migh performance graphics card (RTX 3080)
- Direct capacitive touchscreen
- Supports group discussions & collaborative learning
- Optimal touch interaction with our cloud-based library of real medical images





Picture/Display	
Type:	Industrial
Diagonal screen size:	65" (163 cm)
Panel resolution:	3840 x 2160 (4K UHD)
Optimum resolution:	3840 x 2160 @ 60Hz (HDMI)
Brightness:	700 nit
Contrast ratio (typical):	4000:01:00
Color gamut:	92% (DCI-P3, CIE 1976)
Touch Technology	
Touch Points:	10 simultaneous points (min separation 20 mm)
Sensing Type:	Mutual capacitance 2 layer
Response Time:	16ms
Accuracy:	±1.5mm
Computer	
CPU:	Intel Core i7-12700 processor (2,1 GHz to 4,9 GHz)
GPU:	RTX 3080, 3660T
Memory:	32 GB DDR5
Storage:	256 GB SSD + 1 TB HDD
Wi-Fi Card:	Intel Wi-Fi 6E AX211
Convenience	
Placement:	Vertical (Landscape), Horizontal (Table)
Energy saving functions:	Ambient light sensor, Energy Star® Certified
Ports	
Easy access on table:	3xUSB 3.0, 1xHDMI
Inside cabinet:	1 x Power cable, 1 x RJ45 (GB Ethernet), 6 x USB 2.0, 4 x USB 3.0, 1 x Microphone, 1 x Headphone, 3 x Display- port, 1 x HDMI, 1 x DVI.
	port, 1 x 1101vii, 1 x 0 vi.
Dimensions	poly, 1 A 1 D 1 1 1 1 2 1 1 1 1 1 1 1 1 1 1 1 1 1
Dimensions Bezel thickness:	30 mm horizontal, 30 mm vertical
Bezel thickness:	30 mm horizontal, 30 mm vertical
Bezel thickness:	30 mm horizontal, 30 mm vertical Width: 1430 mm
Bezel thickness:	30 mm horizontal, 30 mm vertical Width: 1430 mm Height: min. 795 mm
Bezel thickness:	30 mm horizontal, 30 mm vertical Width: 1430 mm Height: min. 795 mm Height: max. 1185 mm (in table mode)
Bezel thickness: Set dimensions (W x H x D):	30 mm horizontal, 30 mm vertical Width: 1430 mm Height: min. 795 mm Height: max. 1185 mm (in table mode) Depth: 900 mm (in table mode)
Bezel thickness: Set dimensions (W x H x D): Product weight:	30 mm horizontal, 30 mm vertical Width: 1430 mm Height: min. 795 mm Height: max. 1185 mm (in table mode) Depth: 900 mm (in table mode)
Bezel thickness: Set dimensions (W x H x D): Product weight: Operating conditions	30 mm horizontal, 30 mm vertical Width: 1430 mm Height: min. 795 mm Height: max. 1185 mm (in table mode) Depth: 900 mm (in table mode) 200 kg including PC
Bezel thickness: Set dimensions (W x H x D): Product weight: Operating conditions Temperature range (operation):	30 mm horizontal, 30 mm vertical Width: 1430 mm Height: min. 795 mm Height: max. 1185 mm (in table mode) Depth: 900 mm (in table mode) 200 kg including PC
Bezel thickness: Set dimensions (W x H x D): Product weight: Operating conditions Temperature range (operation): Relative humidity:	30 mm horizontal, 30 mm vertical Width: 1430 mm Height: min. 795 mm Height: max. 1185 mm (in table mode) Depth: 900 mm (in table mode) 200 kg including PC
Bezel thickness: Set dimensions (W x H x D): Product weight: Operating conditions Temperature range (operation): Relative humidity: Power	30 mm horizontal, 30 mm vertical Width: 1430 mm Height: min. 795 mm Height: max. 1185 mm (in table mode) Depth: 900 mm (in table mode) 200 kg including PC 10 - 30 °C 20 - 80 % (noncondensing)
Bezel thickness: Set dimensions (W x H x D): Product weight: Operating conditions Temperature range (operation): Relative humidity: Power Consumption (Max):	30 mm horizontal, 30 mm vertical Width: 1430 mm Height: min. 795 mm Height: max. 1185 mm (in table mode) Depth: 900 mm (in table mode) 200 kg including PC 10 - 30 °C 20 - 80 % (noncondensing)
Bezel thickness: Set dimensions (W x H x D): Product weight: Operating conditions Temperature range (operation): Relative humidity: Power Consumption (Mex): Standby Consumption:	30 mm horizontal, 30 mm vertical Width: 1430 mm Height: min. 795 mm Height: max. 1185 mm (in table mode) Depth: 900 mm (in table mode) 200 kg including PC 10 - 30 °C 20 - 80 % (noncondensing) 1176W <1W
Bezel thickness: Set dimensions (W x H x D): Product weight: Operating conditions Temperature range (operation): Relative humidity: Power Consumption (Max): Standby Consumption: Power Options:	30 mm horizontal, 30 mm vertical Width: 1430 mm Height: min. 795 mm Height: max. 1185 mm (in table mode) Depth: 900 mm (in table mode) 200 kg including PC 10 - 30 °C 20 - 80 % (noncondensing) 1176W <1W
Bezel thickness: Set dimensions (W x H x D): Product weight: Operating conditions Temperature range (operation): Relative humidity: Power Consumption (Max): Standby Consumption: Power Options: Miscellaneous	30 mm horizontal, 30 mm vertical Width: 1430 mm Height: min. 795 mm Height: max. 1185 mm (in table mode) Depth: 900 mm (in table mode) 200 kg including PC 10 - 30 °C 20 - 80 % (noncondensing) 1176W <1W 230V/100V English (US & UK), Simplified Chinese, Danish, Dutch, Finnish, French, German, Greek, Italian, Japanese, Norwegian,
Bezel thickness: Set dimensions (W x H x D): Product weight: Operating conditions Temperature range (operation): Relative humidity: Power Consumption (Max): Standby Consumption: Power Options: Miscellaneous On-Screen Display Languages:	30 mm horizontal, 30 mm vertical Width: 1430 mm Height: min. 795 mm Height: max. 1185 mm (in table mode) Depth: 900 mm (in table mode) 200 kg including PC 10 - 30 °C 20 - 80 % (noncondensing) 1176W <1W 230V/100V English (US & UK), Simplified Chinese, Danish, Dutch, Finnish, French, German, Greek, Italian, Japanese, Norwegian, Polish, Portuguese, Russian, Spanish, Swedish & Turkish.
Bezel thickness: Set dimensions (W x H x D): Product weight: Operating conditions Temperature range (operation): Relative humidity: Power Consumption (Max): Standby Consumption: Power Options: Miscellaneous On-Screen Display Languages: Protection glass:	30 mm horizontal, 30 mm vertical Width: 1430 mm Height: min. 795 mm Height: max. 1185 mm (in table mode) Depth: 900 mm (in table mode) 200 kg including PC 10-30 °C 20-80 % (noncondensing) 1176W <1W 230V/100V English (US & UK), Simplified Chinese, Danish, Dutch, Finnish, French, German, Greek, Italian, Japanese, Norwegian, Polish, Portuguese, Russian, Spanish, Swedish & Turkish. 6 mm hardened clear glass
Bezel thickness: Set dimensions (W x H x D): Product weight: Operating conditions Temperature range (operation): Relative humidity: Power Consumption (Max): Standby Consumption: Power Options: Miscellaneous On-Screen Display Languages: Protection glass: Mobility:	30 mm horizontal, 30 mm vertical Width: 1430 mm Height: min. 795 mm Height: max. 1185 mm (in table mode) Depth: 900 mm (in table mode) 200 kg including PC 10 - 30 °C 20 - 80 % (noncondensing) 1176W <1W 230V/100V English (US & UK), Simplified Chinese, Danish, Dutch, Finnish, French, German, Greek, Italian, Japanese, Norwegian, Polish, Portuguese, Russian, Spanish, Swedish & Turkish. 6 mm hardened clear glass
Bezel thickness: Set dimensions (W x H x D): Product weight: Operating conditions Temperature range (operation): Relative humidity: Power Consumption (Max): Standby Consumption: Power Options: Miscellaneous On-Screen Display Languages: Protection glass: Mobility: Software	30 mm horizontal, 30 mm vertical Width: 1430 mm Height: min. 795 mm Height: max. 1185 mm (in table mode) Depth: 900 mm (in table mode) 200 kg including PC 10 - 30 °C 20 - 80 % (noncondensing) 1176W <1W 230V/100V English (US & UK), Simplified Chinese, Danish, Dutch, Finnish, French, German, Greek, Italian, Japanese, Norwegian, Polish, Portuguese, Russian, Spanish, Swedish & Turkish. 6 mm hardened clear glass 4 pieces of heavy-duty wheels, with locks
Bezel thickness: Set dimensions (W x H x D): Product weight: Operating conditions Temperature range (operation): Relative humidity: Power Consumption (Max): Standby Consumption: Power Options: Miscellaneous On-Screen Display Languages: Protection glass: Mobility: Software Sectra PACS version:	30 mm horizontal, 30 mm vertical Width: 1430 mm Height: min. 795 mm Height: max. 1185 mm (in table mode) Depth: 900 mm (in table mode) 200 kg including PC 10 - 30 °C 20 - 80 % (noncondensing) 1176W <1W 230V/100V English (US & UK), Simplified Chinese, Danish, Dutch, Finnish, French, German, Greek, Italian, Japanese, Norwegian, Polish, Portuguese, Russian, Spanish, Swedish & Turkish. 6 mm hardened clear glass 4 pieces of heavy-duty wheels, with locks

 $^{\,^*\}mbox{Valid}$ from April 2023. All specifications are subject to change.

For more information about your specific computer, visit Dell Support and identify your product using the service tag number that is found on your computer.

